

**Listing of Claims:**

This following listing of claims will replace all prior versions of claims in the application:

1. (Original) A focus detection device comprising:
  - a solid state image sensing device including a first photoelectric conversion element array which photoelectrically converts a first light beam passing through a first area of an exit pupil of a photographing optical system, and a second photoelectric conversion element array which photoelectrically converts a second light beam passing through a second area of the exit pupil which is different from the first area; and
  - a computing device which detects a focus state of the photographing optical system by computing a correlation between a first image signal which is an image signal from the first photoelectric conversion element array and a second image signal which is an image signal from the second photoelectric conversion element array in accordance with a position of a focus detection area in an image sensing frame on the basis of a ratio between a shift amount of a focus detection opening pupil, formed when limitation is imposed by an exit window of the photographing optical system, with respect to an optical axis, and a width of the focus detection opening pupil.
2. (Original) A focus detection method wherein a first light beam passing through a first area of an exit pupil of a photographing optical system is photoelectrically converted by a first photoelectric conversion element array, a second light beam passing through a second area of the exit pupil which is different from the first area is photoelectrically converted by a second photoelectric conversion element array, and a focus state of the photographing optical system is detected by computing a correlation between a first image signal which is an image signal from the first photoelectric conversion element array and a second image signal which is an image signal from the second photoelectric conversion element array in accordance with a position of a focus detection area in an image sensing frame on the basis of a ratio between a shift amount of a focus detection opening pupil, formed when limitation is imposed by an exit window of the photographing optical system, with respect to an optical axis, and a width of the focus detection opening pupil.

3. (Currently amended) A computer program recorded on a computer-readable medium for causing a computer to execute a the focus detection method ~~defined~~ recited in claim 2.
4. (Cancelled).